

LEAD-FREE SOLDER PELLETS/ANODES SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product Identity: Lead-Free Solder (in pellet form or as cast anodes)

Trade Names and Synonyms: LF-2 and LF-3 Grades (this safety data sheet applies to both)

Manufacturer:

Teck Metals Ltd.
Trail Operations
Trail, British Columbia
V1R 4L8
Emergency Telephone: 250-364-4214

Supplier:

Teck Advanced Materials Inc.
13670 Danielson Street
Suite H & I
Poway, CA 92064

Preparer:

Teck Metals Ltd.
Suite 3300 – 550 Burrard Street
Vancouver, British Columbia
V6C 0B3

Date of Last Review: July 24, 2018.

Date of Last Edit: July 24, 2018.

Product Use: Used by the electronics industry in the manufacturing process for computer chips as thermal interfaces or integrated circuits.

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION:

Health	Physical	Environmental
Acute Toxicity (Oral, Inhalation) – Does not meet criteria	Does not meet criteria for any Physical Hazard	Aquatic Toxicity – Long Term – Category 4
Skin Corrosion/Irritation – Does not meet criteria		
Eye Damage/Eye Irritation – Does not meet criteria		
Respiratory or Skin Sensitization – Does not meet criteria		
Mutagenicity – Does not meet criteria		
Carcinogenicity – Does not meet criteria		
Reproductive Toxicity – Does not meet criteria		
Specific Target Organ Toxicity – Does not meet criteria		
Acute Exposure – Does not meet criteria		
Chronic Exposure – Does not meet criteria		

LABEL:

Symbols: None	Signal Word: None
Hazard Statements May cause long-lasting harmful effects to aquatic life.	Precautionary Statements: Avoid release to the environment. Dispose of contents/containers according to local regulations.

Emergency Overview: A solid metal alloy pellet or anode that does not burn in a fire but will melt readily at temperatures above 210°C to form a molten metal pool. This product is relatively non-toxic to humans, and poses little immediate hazard to emergency response personnel or the environment in a fire or transportation emergency response situation.

Potential Health Effects: Pure tin, copper and silver are all relatively non-toxic to humans. In the form in which it is sold this product does not present any significant health hazard to workers. However, it may cause mild local irritation to eyes, nose, throat and upper airways, if the product is heated to the point of fuming. Tin, copper and silver are not listed as carcinogens by OSHA, NTP, IARC, ACGIH or the EU (see Toxicological Information, Section 11).

Potential Environmental Effects: The metals contained in this product could be toxic to aquatic and terrestrial organisms if present in the ionic form. However, in this alloyed form they are not readily bio-available to the environment (see Ecological Information, Section 12).

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS Registry No.	CONCENTRATION (% wt/wt)
----------------------	------------------	-------------------------

Tin	7440-31-5	LF-2 – 95.5% / LF-3 – 94.5%
Silver	7440-22-4	LF-2 – 3.5% / LF-3 – 3.5%
Copper	7440-50-8	LF-2 – 1% / LF-3 – 2%

Note: See Section 8 for Occupational Exposure Guidelines.

SECTION 4. FIRST AID MEASURES

Eye Contact: *Symptoms:* Mild eye irritation, redness. Gently brush product off face if necessary. Do not rub eye(s). Let the eye(s) water naturally for a few minutes. Look right and left, then up and down. If particle/dust does not dislodge, cautiously rinse eye(s) with lukewarm, gently flowing water for 5 minutes or until particle/dust is removed, while holding the eyelid(s) open. If irritation persists, get medical attention/advice. DO NOT attempt to manually remove anything stuck to the eye.

Skin Contact: *Symptoms:* None expected. Wash gently and thoroughly with lukewarm, gently flowing water and non-abrasive soap for 5 minutes, or until product is removed. If skin irritation occurs or you feel unwell, get medical advice/attention.
Molten Metal: Flush contact area to solidify and cool but do not attempt to remove encrusted material or clothing. Cover burns and seek medical attention immediately.

Inhalation: *Symptoms:* Coughing and irritation of the nose and throat on inhalation of fumes. Remove source of exposure or move person to fresh air and keep comfortable for breathing. Seek medical attention if you feel unwell.

Ingestion: *Symptoms:* Stomach upset, nausea. If you feel unwell or are concerned, get medical advice/attention.

SECTION 5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Massive metal is not considered a fire or explosion hazard. However, this alloy has a relatively low melting point (210 – 215°C) and may readily form a molten metal pool when involved in a fire.

Extinguishing Media: Apply dry sand, dolomite, graphite, powdered sodium chloride, or special dry powder extinguishing media (i.e. Class D extinguisher) to any burning ingots or pellets. Do NOT use water, carbon dioxide, foam or Halons with fires involving molten metal.

Fire Fighting: Fire fighters should be fully-trained and wear full protective clothing including an approved, self-contained breathing apparatus which supplies a positive air pressure within a full face piece mask.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Procedures for Cleanup: Control source of spillage if possible to do so safely. Clean up spilled material, observing precautions in Section 8, Personal Protection. Pick up by hand or shovel/scoop up. Return uncontaminated spilled material to the process if possible. Place contaminated material in suitable labelled containers for later recovery or disposal. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

Personal Precautions: Protective clothing, safety glasses and gloves are recommended for persons responding to an accidental release (see also Section 8). Safety type boots are recommended.

Environmental Precautions: In this alloy form, tin, silver and copper have limited bio-availability and pose no immediate ecological risk. However, processing of the product or its extended exposure in aquatic and terrestrial environments may lead to the release of these metals in bioavailable forms. Contamination of water and soil by this product should be prevented.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling: Keep containers closed when not in use. If the material is being heated to fuming, use with adequate ventilation.

Conditions for Safe Storage: Store in a dry, covered area away from incompatible materials. No special packaging materials or handling materials are required.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Guidelines: (*Time-Weighted Average (TWA) concentration over 8 hr unless otherwise indicated*)

<u>Component</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>NIOSH REL</u>
Tin	2 mg Sn/m ³	2 mg Sn/m ³	2 mg Sn/m ³

Silver	0.10 mg Ag/m ³	0.01 mg Ag/m ³	0.01 mg Ag/m ³
Copper	0.2 mg Cu/m ³ (fume)	0.1 mg Cu/m ³ (fume)	0.1 mg Cu/m ³ (fume)
	1.0 mg Cu/m ³ (dust)	1.0 mg Cu/m ³ (dust)	1.0 mg Cu/m ³ (dust)

NOTE: OEGs for individual jurisdictions may differ from those given above. Check with local authorities for the applicable OEGs in your jurisdiction.
 ACGIH - American Conference of Governmental Industrial Hygienists; OSHA - Occupational Safety and Health Administration; NIOSH - National Institute for Occupational Safety and Health. TLV – Threshold Limit Value, PEL – Permissible Exposure Limit, REL – Recommended Exposure Limit.

NOTE: The selection of the necessary level of engineering controls and personal protective equipment will vary depending upon the conditions of use and the potential for exposure. The following are therefore only general guidelines that may not fit all circumstances. Control measures to consider include:

Ventilation: Use adequate local or general ventilation to maintain the concentration of dust and/or fumes in the working environment well below recommended occupational exposure limits for tin, silver and copper. Supply sufficient replacement air to make up for any air removed by the exhaust system.

Protective Clothing: Gloves and coveralls, shop coat or other work clothing with long sleeves are recommended to prevent prolonged or repeated direct skin contact when this solder is processed. Eye protection and safety type boots are also recommended.

Respirators: Where fumes are generated and cannot be controlled to within acceptable levels by engineering means, use appropriate NIOSH-approved respiratory protection equipment (a 42CFR84 Class N, R or P-95 or 100 particulate filter cartridge).

General Hygiene Considerations: Follow good industrial hygiene and housekeeping practices. Do not eat, drink or smoke while working with this material. Thoroughly wash hands before eating, drinking or smoking in appropriate, designated areas.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Silver grey metal	Odour: None	Odour Threshold: Not applicable	pH: Not applicable
Melting Point/Range: 210 – 215°C	Boiling Point/Range: 2270°C (Tin)	Vapour Pressure: Negligible @ 20°C	Vapour Density: Not applicable
Relative Density (Water = 1): 7.3 – 7.4	Evaporation Rate: Not applicable	Partition Distribution (n-octanol/water): Not applicable	Solubility (in water): Insoluble in water
Flammability: Not combustible	Flammable Limits (LEL/UEL): Not applicable	Auto-ignition Temperature: None	Decomposition Temperature: None

SECTION 10. STABILITY AND REACTIVITY

Stability & Reactivity: This material is stable and not considered reactive under normal temperatures and pressures. Hazardous polymerization or runaway reactions will not occur. The alloy oxidizes slowly, especially in the presence of moisture.

Incompatibilities: Avoid contact with strong acids or alkalis. Incompatible with strong oxidizing agents such as chlorine, fluorine, bromine, and interhalogens such as bromine trifluoride, as well as sodium, potassium and barium peroxide, sodium or potassium chlorate, fused ammonium nitrate and turpentine, magnesium, acetylene gas. Avoid generation of dust clouds near open flames, or other ignition sources.

Hazardous Decomposition Products: High temperature operations such as oxy-acetylene cutting and electric arc welding will generate metal oxide fume. The particle size of these metal fumes is largely within the respirable size range, which increases the likelihood of inhalation and deposition of the fume within the body.

SECTION 11. TOXICOLOGICAL INFORMATION

General: Inhalation of fumes generated by melting or flame cutting of lead free solder pellets or anodes would be the only significant route of occupational exposure. Respiratory irritation and possible metal fume fever may result from significant overexposure to lead-free solder fumes.

Acute:

Skin/Eye: Contact with lead-free solder particles or fume may cause local mechanical irritation but would not cause eye tissue damage. There have been limited reports of allergic contact dermatitis following exposure to powdered silver, silver solutions, and dental amalgams.

Inhalation: Acute inhalation of dusts and particularly fumes may result in irritation of the nose, throat and upper respiratory passages. Symptoms may include discomfort, coughing, tingling sensation, sneezing and/or shortness of breath and wheezing. Acute overexposure to copper dust or fume can result in the condition called metal fume fever. The symptoms of metal fume fever will occur within 3 to 10 hours, and include immediate dryness and irritation of the throat, sweet metallic taste, tightness of the chest, and coughing which may later be followed by flu-like symptoms of fever, malaise, perspiration, frontal headache, muscle cramps, low back pain, occasionally blurred vision, nausea, and vomiting. The symptoms are temporary and generally disappear without medical intervention within 24 to 48 hours of onset. There are no recognized complications, after effects, or chronic effects that result from this condition. Extremely high exposures to silver have caused lung damage with pulmonary edema, but this ingredient is present at such a low level that exposures of this magnitude would be unlikely.

Ingestion: Ingestion may irritate the stomach resulting in possible headache, metallic taste, nausea and vomiting.

Chronic: There is no chronic form of metal fume fever but in rare instances an acute incident may be followed by complaints such as bronchitis or pneumonia. Chronic overexposure to tin dust or fumes is known to cause a benign pneumoconiosis (Stannosis) characterized by progressive X-ray changes of the lung while exposure continues, but without any distinctive fibrosis or scarring of the lungs and without any evidence of disability. Prolonged exposure to silver dust may cause a bluish or greyish pigmentation to the skin, eyes and mucous membranes. Copper may also cause skin and hair discoloration. However, both metals are present only at low concentrations in the solder alloy. None of tin, copper or silver is listed as human carcinogens by the Occupational Safety and Health Administration (OSHA), the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the American Conference of Governmental Industrial Hygienists (ACGIH) or the European Union (EU).

Animal Toxicity:

<u>Hazardous Ingredient:</u>	<u>Acute Oral Toxicity:</u>	<u>Acute Dermal Toxicity:</u>	<u>Acute Inhalation Toxicity:</u>
Tin	LD ₅₀ >2,000 mg/kg [†]	LD ₅₀ >2,000 mg/kg*	LC ₅₀ >4.75 mg/L [‡]
Silver	LD ₅₀ >5,000 mg/kg [†]	LD ₅₀ >2,000 mg/kg*	LC ₅₀ >5.16 mg/L [‡]
Copper	LD ₅₀ >5,000 mg/kg ^{††}	LD ₅₀ >2,000 mg/kg*	LC ₅₀ >5.11 mg/L [‡]

[†] LD₅₀, Rat, Oral * LD₅₀, Rat, Dermal [‡] LC₅₀, Rat, Inhalation, 4 hour
^{††} LD₅₀, Mouse, Oral

SECTION 12. ECOLOGICAL INFORMATION

The metals contained in this product are not directly bio-available and pose no immediate ecological risk. However, they may become such through oxidation or processing of the product. Compounds of copper, silver and tin are highly toxic to aquatic and terrestrial organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

If material cannot be returned to process or salvage, dispose of in accordance with applicable regulations.

SECTION 14. TRANSPORT INFORMATION

PROPER SHIPPING NAME TRANSPORT CANADA	Not regulated.
PROPER SHIPPING U.S. DOT.....	Not regulated
TRANSPORT CANADA CLASSIFICATION.....	Not applicable
U.S. DOT CLASSIFICATION	Not applicable
PRODUCT IDENTIFICATION NUMBER	Not applicable
MARINE POLLUTANT.....	No
IMO CLASSIFICATION	Not regulated

SECTION 15. REGULATORY INFORMATION

U.S.
INGREDIENTS LISTED ON TSCA INVENTORY..... Yes
HAZARDOUS UNDER HAZARD COMMUNICATION STANDARD No

CERCLA SECTION 103 HAZARDOUS SUBSTANCES.....	Tin.....No	RQ: N/A
	Copper.....Yes	RQ: 5,000lbs.
	Silver.....Yes	RQ: 1,000lbs.

* reporting not required when diameter of the pieces of solid metal released is equal to or exceeds 100 micrometers.

EPCRA SECTION 302 EXTREMELY HAZARDOUS SUBSTANCE.....	No ingredients qualify.
EPCRA SECTION 311/312 HAZARD CATEGORIES.....	No hazard categories apply.
EPCRA SECTION 313 TOXIC RELEASE INVENTORY:	Copper.. CAS No. 7440-50-8 ... Percent by weight: 1 – 2%
	Silver CAS No: 7440-22-4 ... Percent by weight: 3.5%

SECTION 16. OTHER INFORMATION

Date of Original Issue: March 06, 2013

Version: 01 (*first edition*)

Date of Latest Revision: July 23, 2018

Version: 02

The information in this Safety Data Sheet is based on the following references:

- American Conference of Governmental Industrial Hygienists, 2004, Documentation of the Threshold Limit Values and Biological Exposure Indices, Seventh Edition including updates.
- American Conference of Governmental Industrial Hygienists, 2018 Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices.
- American Conference of Government Industrial Hygienists, 2018, Guide to Occupational Exposure Values.
- Bretherick's Handbook of Reactive Chemical Hazards, 20th Anniversary Edition (P. G. Urben, Ed.) 1995.
- Canadian Centre for Occupational Health and Safety (CCOHS) CHEMINFO Chemical Substance On-Line Data Base (last accessed 12 July 2018).
- Commission de la santé et la sécurité du travail, Service du répertoire toxicologique, Étain (Tin), 2000-01.
- European Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006 (REACH).
- Handbook on the Toxicology of Metals, 3rd Ed., Gunnar F. Nordberg, Bruce A. Fowler, Monica Nordberg and Lars Friberg, Editors, Academic Press, New York, NY (2007) Chapter 39 – Silver & Chapter 42 – Tin.
- Industry Canada, SOR/2015-17, Hazardous Products Regulations, 11 February 2015.
- International Chemical Safety Cards (WHO/IPCS/ILO), ICSC: 1535: Tin Metal (Oct 2004).
- Merck & Co., Inc., 2001, The Merck Index, An Encyclopedia of Chemicals, Drugs, and Biologicals, Thirteenth Edition.
- National Library of Medicine, National Toxicology Information Program, Hazardous Substance Data Bank
- Patty's Toxicology, 5th Edition, (E. Bingham, B. Cohrssen & C.H. Powell, Ed.) 2001.
- U.S. Dept. of Health and Human Services, National Institute for Occupational Safety and Health, NIOSH Pocket Guide to Chemical Hazards. CD-ROM Edition September 2005.
- U.S. Occupational Safety and Health Administration, 1989, Code of Federal Regulations, Title 29, Part 1910.

Acronyms not spelled out elsewhere in the SDS:

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

EPCRA: Emergency Planning and Community Right- to-Know Act

IMO: International Maritime Organization

LD50, LC50: Lethal Dose 50%, Lethal Concentration 50%

OEGs: Occupational Exposure Guidelines

TSCA: Toxic Substances Control Act

Wt: Weight

Notice to Reader

Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. Teck Advanced Materials Inc. extends no warranty and assumes no responsibility for the accuracy of the content and expressly disclaims all liability for reliance thereon. This safety data sheet provides guidelines for the safe handling and processing of this product; it does not and cannot advise on all possible situations. Therefore, your specific use of this product should be evaluated to determine if additional precautions are required. Individuals exposed to this product should read and understand this information and be provided pertinent training prior to working with this product.